

CSS2 Test Suite: 12.5 counter-increment

[\[index page\]](#) [\[section\]](#) [\[Previous\]](#) [\[Next\]](#) [\[Specification\]](#)

The style declarations contained within this page:

```
span:before {content: counter(ct1) "|" counter(ct2) "|" counter(ct3) "... "};  
li span:before {counter-increment: ct1;}  
li li span:before {counter-increment: ct2 2;}  
li li li span:before {counter-increment: ct3 -3;}
```

The list items in the following set of lists all have 'span' elements, and each 'span' should be preceded with generated content in the form "a|b|c... " where the letters are incremented numbers. "a" numbers increment in ones, "b" in twos, and "c" in negative threes. Note that counters are **not** reset for each sublist, or at any point, and so should use the default '0' as their base point.

- 1|0|0... list item
- 2|0|0... list item
- 3|0|0... list item
 - 3|2|0... list item
 - 3|4|0... list item
 - 3|6|0... list item
 - 3|6|-3... list item
 - 3|8|-3... list item
 - 3|10|-3... list item
 - 3|10|-6... list item
 - 3|10|-9... list item
 - 3|10|-12... list item
 - 3|10|-15... list item
 - 3|12|-15... list item
 - 3|14|-15... list item
- 4|14|-15... list item
- 5|14|-15... list item

[\[index page\]](#) [\[section\]](#) [\[Previous\]](#) [\[Next\]](#) [\[Specification\]](#)
